

M30 Cylindrical Capacitive Proximity Sensor

BCDS-M30-A14F20-S124 series · Sensing Distance: 20mm(Flush) · Switching Freq.: 25Hz/25Hz AC,40Hz DC

IP67
Ingress Protection



①



②

KEY SPECIFICATIONS

SENSING DISTANCE **20mm(Flush)**	SWITCHING FREQ. **25Hz/25Hz AC,40Hz DC**
AMBIENT TEMP. **-25...70°C**	HOUSING **M30*1.5mm**
INGRESS PROTECTION **IP67**	

FEATURES

- Potentiometer for sensitivity adjustment
- Detecting non-metals
- Detection of non-metallic objects depends on the dielectric constant of the object

MODEL CODES

Output Type	①	②
AC type — 20...250V AC · 25Hz		
N.O	**BCDS-M30-A14F20-S124** SKU 10102825	**BCDP-M30-A14F20-S124** SKU 10102829
N.C	**BCDS-M30-A24F20-S124** SKU 10102826	**BCDP-M30-A24F20-S124** SKU 10102830
AC/DC type — 20...250V AC/DC · 25Hz AC,40Hz DC		
N.O	**BCDS-M30-U15F20-S124** SKU 10102827	**BCDP-M30-U15F20-S124** SKU 10102831
N.C	**BCDS-M30-U25F20-S124** SKU 10102828	**BCDP-M30-U25F20-S124** SKU 10102832


TECHNICAL DATA

Exterior structure	M30*1.5mm
Sensing distance	20mm(Flush)
Switching frequency	AC: 25Hz · AC/DC: 25Hz AC,40Hz DC
Operating voltage	AC: 20...250V AC · AC/DC: 20...250V AC/DC
Voltage drop	<9V AC(300mA)/<10V AC,<8V DC
Load current	Max.load: 300mA; min.Load: 5mA
Residual signal	<2.5mA
Hysteresis	<15%(Sr)
Repeatability	<5.0%(Sr)
Switch protection	Short-circuit protection, Polarity reversal protection, Power-on

LED indicator	With (Action: LED Indicator Lights Up)
Ambient temperature	-25...70°C
Ingress protection	IP67
Housing material	①: Brass, nickel-plated ②: PBT
Sensing face material	PBT
Connection	M12 Connector
Accessories	M12 4 pin cable with connector

DIMENSIONAL DRAWINGS

M30X90 Connector ①



All dimensions in mm.