M18 Cylindrical Inductive Proximity Sensor — Factor 1

BIDF-M18-F8.0-PC2-S124 series · Sensing Distance: 8mm(Flush) · Operating Voltage: 10...30VDC(±10%)

IP67
Ingress Protection



①



②

KEY SPECIFICATIONS

SENSING DISTANCE **8mm(Flush)**	OPERATING VOLTAGE **10...30VDC(±10%)**
SWITCHING FREQ. **2000Hz**	AMBIENT TEMP. **-25...70°C**
HOUSING **M18*1mm**	INGRESS PROTECTION **IP67**

FEATURES

- Factor 1: equal sensing distance on all metals
- Detection of copper, iron, aluminum
- Application in the automotive industry

MODEL CODES

Output Type	①	②
NPN N.O	**BIDF-M18-N11F8.0-PC2** SKU 10103776	**BIDF-M18-N11F8.0-S124** SKU 10103780
NPN N.C	**BIDF-M18-N21F8.0-PC2** SKU 10103777	**BIDF-M18-N21F8.0-S124** SKU 10103781
PNP N.O	**BIDF-M18-P11F8.0-PC2** SKU 10103778	**BIDF-M18-P11F8.0-S124** SKU 10103782
PNP N.C	**BIDF-M18-P21F8.0-PC2** SKU 10103779	**BIDF-M18-P21F8.0-S124** SKU 10103783


TECHNICAL DATA

Exterior structure	M18*1mm
Sensing distance	8mm(Flush)
Switching frequency	2000Hz
Operating voltage	10...30VDC(±10%)
Voltage drop	≤2.0V
Load current	200mA
Leakage current	≤0.01mA
No-load current	≤10mA(24V)
Hysteresis	<15%(Sr)
Repeatability	<1.0%(Sr)
Switch protection	Short-circuit protection, Polarity reversal protection, Power-on


LED indicator	With (Action: LED Indicator Lights Up)
Ambient temperature	-25...70°C
Ingress protection	IP67
Housing material	Brass, nickel-plated
Sensing face material	PPS
Connection	①: 2m PVC Cable, 3*0.35mm² ②: M12 Connector
Accessories	①: None ②: M12 4 pin cable with connector

DIMENSIONAL DRAWINGS

M18X55 Cable ①



M18X79 Connector ②



All dimensions in mm.