M18 Cylindrical Inductive Proximity Sensor

BIDW-M18-F8.0-UC2-S-S124 series · Sensing Distance: 8mm(Flush) · Operating Voltage: 10...30VDC(±10%)

IP67
Ingress Protection



KEY SPECIFICATIONS

SENSING DISTANCE **8mm(Flush)**	OPERATING VOLTAGE **10...30VDC(±10%)**
SWITCHING FREQ. **3000Hz**	AMBIENT TEMP. **-40...85°C**
HOUSING **M18*1mm**	INGRESS PROTECTION **IP67**

FEATURES

- Low temperature resistance
- Suitable for cold storage, extremely cold environment
- Temperature-40°C...85°C

MODEL CODES

Output Type	①	②	③	④
NPN N.O	**BIDW-M18-N11F8.0-UC2** SKU 10103845	**BIDW-M18-N11F8.0-UC2-S** SKU 10103849	**BIDW-M18-N11F8.0-S124** SKU 10103853	**BIDW-M18-N11F8.0-S124-S** SKU 10103857
NPN N.C	**BIDW-M18-N21F8.0-UC2** SKU 10103846	**BIDW-M18-N21F8.0-UC2-S** SKU 10103850	**BIDW-M18-N21F8.0-S124** SKU 10103854	**BIDW-M18-N21F8.0-S124-S** SKU 10103858
PNP N.O	**BIDW-M18-P11F8.0-UC2** SKU 10103847	**BIDW-M18-P11F8.0-UC2-S** SKU 10103851	**BIDW-M18-P11F8.0-S124** SKU 10103855	**BIDW-M18-P11F8.0-S124-S** SKU 10103859
PNP N.C	**BIDW-M18-P21F8.0-UC2** SKU 10103848	**BIDW-M18-P21F8.0-UC2-S** SKU 10103852	**BIDW-M18-P21F8.0-S124** SKU 10103856	**BIDW-M18-P21F8.0-S124-S** SKU 10103860

TECHNICAL DATA

Exterior structure	M18*1mm
Sensing distance	8mm(Flush)
Switching frequency	3000Hz
Operating voltage	10...30VDC(±10%)
Voltage drop	≤2.0V
Load current	200mA
Leakage current	≤0.01mA
No-load current	≤10mA(24V)
Hysteresis	<15%(Sr)
Repeatability	<1.0%(Sr)
Switch protection	Short-circuit protection, Polarity reversal protection, Power-on
LED indicator	With (Action: LED Indicator Lights Up)

Ambient temperature	-40...85°C
Ingress protection	IP67
Housing material	Brass, nickel-plated
Sensing face material	PBT
Connection	①: 2m PUR Cable, 3*0.35mm² ②: 2m PUR Cable, 3*0.35mm² ③: M12 Connector ④: M12 Connector
Accessories	①: None ②: None ③: M12 4 pin cable with connector ④: M12 4 pin cable with connector

DIMENSIONAL DRAWINGS

M18X55 Cable ①



M18X35 Cable ②



M18X79 Connector ③



M18X48 Connector ④



All dimensions in mm.